FROST LINE DEPTH= 42"

WINTER DESIGN TEMP= -4' F

TERMITE = MODERATE TO HEAVY

REPORT, & THE NAME AND VERSION OF THE COMPLIANCE SOFTWARE TOOL.

CLIMATE ZONE 5 AND MARINE 4.

\*REFER TO FLOOR PLANS AND TYPICAL WALL SECTION FOR INSULATION R-VALUE REQUIREMENTS.

GRADE B, Fy=36 KSI, AND HIGH-STRENGTH BOLTS, NUT, AND WASHERS PER ASTM A325 WITH 1/3"

3. ALL STEEL SHALL BE FABRICATED, DETAILED, AND ERECTED IN ACCORDANCE WITH AISC SPECIFICATIONS,

DIAMETER MINIMUM LINLESS NOTED OTHERWISE

15.3. IN THE EVENT THAT THE HOOD EXHAUST IS GREATER THAN 400 CFM. THEN THE CONTRACTOR SHALL

PROVIDE MAKEUP AIR AT A RATE APPROXIMATELY EQUAL TO THE EXHAUST AIR RATE. SUCH MAKE AIR 2.

SYSTEMS SHALL BE EQUIPPED WITH A MEANS OF CLOSURE AND SHALL BE AUTOMATICALLY CONTROLLED

WIND VELOCITY HEATING= 8.4 MPH

WIND VELOCITY COOLING= 5.7 MPH

COINCIDENT WET BULB= 76

OF 5 SHEETS

© 2025 by Craftstone Architects, Inc.







