



STANDARD PAVEMENT SECTION

1 1/2" HOT-MIX ASPHALT SURFACE COURSE MIXTURE D, N70**
2 1/2" HOT-MIX ASPHALT BINDER COURSE L-19.0, N70**
BITUMINOUS MATERIALS PRIME COAT, SS-1 (0.10 gal/sy)**
BITUMINOUS MATERIALS PRIME COAT, PG58-22 (0.35 gal/sy)**
8" AGGREGATE BASE COURSE, TYPE B CA-6 (CRUSHED)
COMPACTED SUBGRADE (95% STANDARD PROCTER DENSITY)

• SHALL BE IN ACCORDANCE WITH SECTION 351 & 406 OF THE IDOT STANDARD SPECIFICATIONS
** NOT INCLUDED IN CONTRACT

LEGEND

■ DENOTES NEW STANDARD PAVEMENT SECTION
— DENOTES COMBINATION CONCRETE CURB & GUTTER (B-6.12)
▨ DENOTES LANDSCAPING AND RESTORATION BY TWP.
• SEEDING CLASS 2A
• EROSION CONTROL BLANKET
• NITROGEN, PHOSPHORUS, POTASSIUM FERTILIZER NUTRIENTS
▬ DENOTES DEPRESSED CONCRETE CURB & GUTTER (B-6.12)

NOTES:

1. ALL PAVEMENT MARKINGS SHALL BE PAINT (YELLOW UNLESS OTHERWISE NOTED) IN ACCORDANCE WITH SECTION 780 OF IDOT SPECIFICATIONS. REFER TO IDOT STANDARD 780001-05 TYPICAL PAVEMENT MARKINGS.
2. ALL DIMENSIONS ARE TO EDGE OF PAVEMENT UNLESS OTHERWISE NOTED.
3. ALL CURB & GUTTER SHALL BE TYPE B6.12 UNLESS OTHERWISE NOTED.
4. REFER TO IDOT TRAFFIC CONTROL STANDARD DETAILS LOCATED HEREIN FOR TRAFFIC CONTROL & PROTECTION REQUIRED FOR WORK WITHIN WCDOT AND/OR IDOT R.O.W.
5. ALL MECHANICAL EQUIPMENT (ROOF OR GROUND MOUNTED) MUST BE FULLY SCREENED.
6. THE INCREASED DETENTION REQUIRED FOR THE ADDED PROPOSED IMPERVIOUS AREA OF 16,580 SQ FT (0.381 ACRES) WILL BE ACCOUNTED FOR IN THE OVERALL DETENTION AS PART OF THE GORMAN DEVELOPMENT.

ACCESSIBILITY SYMBOL

8" DIAM.
1'-4"
1'-10"
1'-10"
1'-2"
1'-10"
14" R
4" PAINTED LINE (TYP.)

NO.	DATE	BY	REVISION DESCRIPTION
1	2/9/23	HRG	PERMIT SUBMITTAL
2	5/18/23	HRG	PERMIT SUBMITTAL

HRGreen.com
HRGreen

WHEATLAND TOWNSHIP PARKING LOT IMPROVEMENTS
WHEATLAND TOWNSHIP ILLINOIS
SITE PLAN

BAR IS ONE INCH ON OFFICIAL DRAWINGS
0" 1"
IF NOT ONE INCH, ADJUST SCALE ACCORDINGLY

DRAWN BY: _____
APPROVED: _____
JOB DATE: 2022
JOB NO: 220744

DRAWING
C05

EXHIBIT C